

# **ABS M5 Kit Clubsport**



- Suitable for front-wheel, rear-wheel and fourwheel drive vehicles
- ► Generic wiring harness to fit all engine bay and front foot well locations for the hydraulic mod-
- ▶ Same ABS hardware as standard ABS M5 Kit

The ABS M5 Kit Clubsport is developed for the operation in front-, rear- or 4-wheel drive vehicles. A generic wiring harness is included in the kit. This enables us to provide the kit with a significantly reduced price in comparison to the standard ABS M5 Kit with individual loom.

The ABS M5 Kit Clubsport is specifically adapted for motorsport use. Individual car parameters like e.g. vehicle weight, vehicle track, wheel weights, wheel circumferences, wheel base or number of increments can be calibrated with software free of charge. Please contact your Bosch Motorsport dealer for further information.

## **Technical Specifications**

#### **Mechanical Data**

Hydraulic unit with attached ECU		
Serial housing, dust- and damp-proof		
Vibration damped circuit board		
38 pin connector		
2 hydraulic valves per wheel		
2 brake circuits (front and rear)		
2 hydraulic high pressures pumps		
2 hydraulic accumulators 5 cm³/each		
Standard fittings	2 x master cylinders M12 x 1 4 x brake cylinders M10 x 1	
Size	122 x 110 x 122 mm	
Weight	1,910 g	
Operating temperature	-30 to 130°C	

Max. shock	50 g less than 6 ms	
Electrical Data		
Supply voltage	10 to 16 V, max. 24 V for 5 min	
Max. peak voltage	35 V for 200 ms	
Power consumption Pump	230 W	
Power consumption Relay	170 W	
Power consumption Electronics	8 W	
Inputs		
4 active wheel speed DF11i, DF11S or DF11V		
Brake pressure (front brake circuit / rear brake circuit)		
Longitudinal acceleration, lateral acceleration, yaw rate (MM5.10 sensor)		
11 adjustment settings		
ABS function can be deactivated (Pos. 12)		
Outputs		
ABS warning light (MIL)		
TTL wheel speed signal FL / FR / RL / RR		
Communication		
ABS and Yaw Rate Sensor	CAN1	
Diagnostics	MSA Box II	

## **Content of Kit and Weights**

	,
Hydraulic unit with attached ECU	1,910 g
2 pressure sensors	40 g/each
Yaw/acceleration sensor	60 g
12 position function switch	50 g

4 wheel speed sensors DF11 standard	50 g/each
ABS warning light (MIL)	50 g
Standard wiring harness	1,540 g
Mounting and vibration-damping boards	80 g
Mounting board for hydraulic unit	212 g

## **Optional Accessories**

Data logger C 70	F 02U V02 302-01
Display DDU 9	F 02U V02 300-02
Display DDU 10	F 02U V02 659-01
Communication interface MSA Box II	F 02U V00 327-03
Wheel speed signal splitter with 1 motorsport connector	F 02U V01 928-01

## **Ordering Information**

## **ABS M5 Kit Clubsport**

DF11i, 500 kbaud

Order number F 02U V05 291-01

## ABS M5 Kit Clubsport

DF11i, 1 Mbaud

Order number F 02U V05 292-01

#### **ABS M5 Kit Clubsport**

DF11S, 500 kbaud

Order number F 02U V05 293-01

## **ABS M5 Kit Clubsport**

DF11S, 1 Mbaud

Order number F 02U V05 294-01

## **ABS M5 Kit Clubsport**

DF11V, 500 kbaud

Order number F 02U V05 295-01

## **ABS M5 Kit Clubsport**

DF11V, 1 Mbaud

Order number F 02U V05 296-01

#### Represented by:

Europe: Bosch Engineering GmbH Bosch Engineering GmbH Motorsport Robert-Bosch-Allee 1 74232 Abstatt Germany Tel.: +49 7062 911 9101 Fax: +49 7062 911 79104 motorsport@bosch.com

www.bosch-motorsport.de

North America: Bosch Engineering North America Bosch Engineering North America Motorsport 38000 Hills Tech Drive Farmington Hills, MI 48331-3417 United States of America Tel.: +1 248 876 2977 Fax: +1 248 876 7373 motorsport@bosch.com www.bosch-motorsport.com

Asia-Pacific: Bosch Engineering Japan K.K. Motorsport 18F Queen's Tower C, 2-3-5 Minato Mirai Nishi-ku, Yokohama-shi Kanagawa 220-6218 Japan Tel.: +81 45 650 5610 Fax: +81 45 650 5611

www.bosch-motorsport.jp

Australia, New Zealand and South Robert Bosch Pty. Ltd Robert Bosch Pty. Ltd Motorsport 1555 Centre Road Clayton, Victoria, 3168 Australia Tel.: +61 (3) 9541 3901 motor.sport@au.bosch.com